

TABLE PURSUANT TO CT6.42# - YARDING/SKIDDING REQUIREMENTS (04/2003)

<u>YARDING/SKIDDING REQUIREMENTS</u>	<u>CUTTING UNIT</u>
Tree length logging is prohibited.	4,5,10 and portions of 6 and 8.
Harvester/Forwarder (cut-to-length) equipment. All equipment will stay on approved trails, all trails will be a minimum of 50 feet apart, and no wider than 12 feet in width.	4,5,6,8,10
Included Timber on slopes less than 35 percent shall be carried free of the ground by a Log Forwarder. Stumps shall not be grubbed from forwarder roads except for portions requiring excavation for safety. All excavation and any supplemental skidding of Included Timber shall be flagged and preapproved in writing prior to commencing such activity.	4,5,6,8,10
All harvest equipment will not leave approved Equipment trails. Equipment trails will be approved In advance by Forest Service. Trails will avoid wet areas and dry draw bottoms, except at approved crossings.	All Units
Tractor/Skidder; Logs can be winched to the skid trail. One end must be suspended when transported to the landing	1,3,6,7,8,9
Tractor skid trails will be an average of 100 feet apart.	1,3,6,7,8,9
Whole tree yarding will be required in all tractor units.	1,3,7,9 and portions of 6 and 8.
Cable-Yoder/skyline; Corridor spacing will be a minimum of 100 feet at point of maximum lateral yarding. Corridor width will be a maximum of 12 feet. Full suspension is required over stream courses and buffers. One end suspension is required during inhaul.	1,2,6,8
Loader used for shoveling the trees will be restricted to the trails that trees are felled on (100') spacing. Trees will be lifted off ground when shuttling them along the skid trail.	8,10

YARDING/SKIDDING EQUIPMENT

CUTTING UNIT

The Log Forwarder shall be all wheel drive, self-propelled, capable of self loading and unloading, and have rear tires or track type traction devices greater than 24 inches in overall width. Log forwarders with GVW's greater than 15,000 pounds shall have a minimum of three load bearing axles.

4,5,6,8,10

Cable yarding system with lateral yarding capabilities. One end suspension, except full log suspension within 100 feet each side of the designated streamcourses.

1,2,6,8